



This dump truck is equipped with an electronically controlled engine and an automatic transmission, with more convenient control and higher efficiency.

Large tonnage engineering axles as well as engineering-specific tires and a 50m³ large volume container.

Adopt the whole machine optimization design scheme of Tonly core technology, with stable performance, reliable quality and attendance rate of above 90%.

TL89 Series off-road dump truck							
Overall parameters	Model	TL897	TL891	Axle	Manufacturer / Country	Hande/China	
	Brand	Tonly		Axie	Load/T	30+50+50	30+50+50
	Drive mode	6×4	6×4	Tires / Rims	Tire model	480/95R29	480/95R29
	GVW (t)	135	135		Rim size	13.00/2.5-29	13.00/2.5-29
	Rated payload (t)	90	90	Container	Base plate material/thickness (mm)	NM400/16	NM400/16
	Kerb weight (t)	45	45		Rear plate material/thickness (mm)	NM400/10	NM400/12
	Dimensions (mm)	10180×3950×4420	10180×3950×4420		Front plate material/thickness (mm)	T700/12	T700/12
	Wheelbase (mm)	4175+1900	4175+1900		Side plate material/thickness (mm)	T700/10	T700/10
	Wheel track (mm)	3100/2850	3100/2850		Container volume (m³)	50	50
	Minimum ground clearance (mm)	410	410	Hydraulic system	Model	FEA214	FEA214
	Minimum turning radius (m)	12	12		Manufacturer / Country	HYVA/China	
	Maximum height of bucket lift (mm)	9380	9380		Steering device	Hydraulic steering	Hydraulic steering
	Maximum angle of bucket lift (°)	48	48		Container lift time (s)	24	24
	Loading height (mm)	4020	4020		Container descent time (s)	24	24
	Braking distance (m)	18	18		Empty load		
	Maximum climbing degree (%)	≥30	≥30	Weight	Front axle (kg)	15000	15000
	Maximum speed (km/h)	45	45		Rear axle (kg)	30000	30000
Engine	Model	QSM15-770-30	QSM15-770-30		Total weight (50% fuel) (kg)	45000	45000
	Manufacturer / Country	DCEC/China		distribution	Loaded		
	Power (hp/kw)	770/566	770/566		Front axle (kg)	30000	30000
Transmission	Model	semi-auto (8DS280+	8DS280		Rear axle (kg)	105000	105000
	Wodel	torque convertor)	0D3200		Total weight (kg)	135000	135000
	Manufacturer / Country	Fast/China		1	1	1	1