



类别 Description		单位 Unit	QYS-5 II	QYS-6.3 III	QYS-8 III A	QYS-10 III	QYS-12 III	QYS-12 N	QYS-16 II
性能 Parameter	最大起升载荷 Max.Lifting Capacity	kg	5000	6300	8000	10000	12000	12000	16000
	最大起重力矩 Max.Lifting Moment	kN.m	125	154.5	240	300	360	360	420
	最大起升高度 Max.Lifting Height	m	8.9	10.8	12.3	13.5	14.2	15.2	17.8
	最大工作幅度 Max.Working Radius	m	8.2	10.3	12.2	13.4	13.5	14.2	17.6
	起重能力 Lifting capacity/ working radius	kg/m	5000/2.5 3350/3.5 1300/5.8 1100/8.2	6300/2.5 4000/3.7 1800/6.0 600/10.3	8000/3.0 5000/4.2 2500/6.9 1100/12.2	10000/3.0 6000/4.5 3000/7.6 1300/13.4	12000/3.0 7300/4.8 3900/7.8 1600/11.5	12000/3.0 8300/4.2 4700/6.8 2900/9.3	16000/2.6 5500/5.1 3100/8.3 1700/11.5
吊臂 Boom	伸缩臂节数 Sections of Boom		2	3	3	3	3	4	4
卷扬机构 Hoisting Device	吊钩速度 Hook speed	m/min	6.8	5	6	6	6	6	6.5
回转机构 Slewing mechanism	钢丝绳 Cable wire	NA T6 × 19W+NF17 70 ZS	Φ 11 × 53	Φ 11 × 64	Φ 11 × 105	Φ 12 × 110	Φ 14 × 100		Φ 16 × 125
	类型 Type		马达驱动、直齿减速、内置机械制动 Motor driven, inner brake			马达驱动、行星齿轮减速、内置液压制动及锁阀 Motor driven, planetary gear reducing, inner hydraulic brake and lock valve.			
支腿 Outrigger	回转变范围/速度 Slewing scope/speed		± 360°, 连续回转/≤ 3r/min continuous						
	类型 Type		马达驱动, 蜗轮蜗杆减速 Motor Driven, Worm gear and rod reducing			马达驱动、行星齿轮减速、内置液压制动及锁阀 Motor driven, planetary gear reducing, inner hydraulic brake and lock valve.			
液压系统 Hydraulic System	前 Front	动作方式 Action	液压/2.2-4.6 Hydraulic		液动/2.2-5.1 Hydraulic		液动/2.2-5.5 Hydraulic		液动/2.29-7.0 Hydraulic
	后 Rear		固定/2.3 Fixed		液动/2.2-3.2 Hydraulic		液动/2.2-4.2 Hydraulic		液动/2.2-4.2 Hydraulic
其他 Others	跨距(m) Span		50		63		80		100
	额定流量 Rated Flow	L/min	50		63		80		100
其他 Others	额定压力 Rated Pressure	MPa	17.5	18	20				20
	液压油箱容量 Oil Tank Capacity	L	115		150		250		320
安全装置 Safe Device	可用底盘(载质量) Chassis Requirement	ton	8t以上 8t or bigger		9t以上 9t or bigger		15t以上 15t or bigger		20t以上 20t or bigger
	安全装置 Safe Device		液压系统安全溢流阀 / 各油缸均设平衡阀或液锁阀 / 卷扬机构内置自动机械或液锁阀 / 钢丝绳过卷报警装置或保护装置(选装) / 起重力矩保护器(选装) / 回转限位装置(选装) Relief valve for the hydraulic system/balance valve or hydraulic lock for each cylinder/auto mechanical or hydraulic brake for hoisting device/overwind alarm (optional)/moment protector(optional)/slewing limit(optional)						

表中参数如有调整, 恕不另行通知。We are regret not to give a notice if the data above will change.

Truck Mounted Crane QYS-6.3III

www.wme.cn/TruckMountedCrane/