



## G series - Clean Water Pumps

MBP15G, MBP20G, MBP30G, MBP40G

- Designed for drainage and irrigation demand in agriculture applications.
- With multiple models and equipment's, economical and practical.
- Widely used in agricultural, gardening, engineering etc.

## H series - High Pressure Water Pumps

MBP15H, MBP20H

- High-performance design for high lift applications.
- Practical design of the impeller for improved lifting performance of the pump.
- Widely used in agriculture and gardening fields for high lift water applications.



## T series - Trash Pump

MBP30T

- Specially designed for comprehensive sewage draining.
- Able to pump soft particles up to 30mm and Sewage water up to 30% solids.
- Double suspension design provides stability.

Model number	MBP15G	MBP20G	MBP30G	MBP40G	MBP15H	MBP20H	MBP30T
Dimension	445x350x355mm	485x365x395mm	505x400x420mm	635x500x590mm	505x400x420mm	505x440x420mm	550x440x455mm
Net weight	22kg	26kg	30kg	50kg	33kg	33kg	48kg
Engine model	GT241	GT400	GT600	GT1000	GT600		
Type	Air cooled 4 stroke OHV single cylinder Mitsubishi gasoline engine						
Displacement	79.6cc	126cc	181cc	296cc	181cc		
Fuel type	Unleaded gasoline						
Tank capacity	1.5L	2.5L	3.8L	6.0L	3.8L		
Lube capacity	0.4L	0.6L	0.6L	1.2L	0.6L		
Ignition system	Breakerless ignition type						
Starting system	Manual recoil starter						
Pump							
Outlet Dia.	1.5"	2.0"	3.0"	4.0"	1.5"/1.0"/1.0"	2.0"/1.5"/1.5"	3.0"
Inlet Dia.	1.5"	2.0"	3.0"	4.0"	1.5"	2.0"	3.0"
Max. flow	21 m <sup>3</sup> /h	30 m <sup>3</sup> /h	60 m <sup>3</sup> /h	80 m <sup>3</sup> /h	20 m <sup>3</sup> /h	30 m <sup>3</sup> /h	45 m <sup>3</sup> /h
Max. lift	22m	28m	30m	25m	55m	60m	25m
Suction	7m	7m	7m	7m	6m	6m	7m
Self priming	≤140s	≤210s	≤210s	≤240s	≤210s	≤150s	≤240s
Speed	3600/rpm						