



Parameter			
Item	Unit	XGA20ACK	XGA20ACK-Li
SIZE			
a Overall length (stowed)	mm	8490	
Overall length (transport)	mm	7900	
b Overall width	mm	2490	
c Overall height	mm	2380	
Platform dimension	mm	1830 × 760 × 1150	
d Wheelbase	mm	2500	
Max. working height	mm	20600	
Max. platform height	mm	18600	
Max. outreach	mm	11980	
Performance			
Max. load capacity	kg	256 (unrestricted) / 350 (restricted)	
Driving speed (stowed)	km/h	4.8	
Driving speed (lifted/extended)	km/h	0.6	
Boom 1 luffing range	°	0~72	
Boom 2 luffing range	°	0~73	
Boom luffing angle	°	/	
Slewing angle of turntable	°	360连续	
Tail swing	mm	560	
Platform rotation angle	°	160	
Min. turning radius (outer)	mm	5000	
Gross machine weight	kg	9100	
Max. gradeability (counterweight up)	%	30	
Max. gradeability (counterweight down)	%	45	
Max. side slope	%	25	
Power Source			
Battery	Ah/V	400/48 DC (Standard)	(412~460 / 51.2 Lithium, Opt
Power unit	Kw/V	12 / 32 AC	12 / 32 AC
Auxiliary power unit	Kw/V	1.9 / 12 DC	1.9 / 12 DC
Drive motor	Kw/V	3.3 / 32 AC	3.3 / 32 AC
Drive	/	/	/
Standard Configuration		1.83m × 0.76m work platform, 12V DC auxiliary power, 4-wheel drive (standard), axle balance, emergency power unit, automatic platform levelling, 360° continuous turntable slewing, pre-interface for telematics, active safety protection system, thumb joystick steering	
Optional Configuration		Tool tray, working light kit	

