

德福 DEF30

主要适配 main adaptation:

70 ~ 120 马力高端拖拉机
1.3 ~ 2.0 吨高端装载机
6.0 ~ 10 吨轮挖
3.0 ~ 5.0 吨叉车
植保机、玉米收、旋耕机
钻机、空压机、发电机组等，具备欧五出口证书。

70 ~ 120 HP high-end tractor
1.3 to 2.0 ton high-end loaders
6.0 ~ 10 tons wheel digging
3.0 to 5.0 tons forklift
Plant protection machine, corn harvester, rotary cultivator
Drilling machine, air compressor, generator set, etc., with Euro V export certificate.



主要性能参数 Main performance parameters

机型 Model	DEF30T	DEF30C
发动机型式 Engine type	立式、直列、水冷、四冲程 Vertical, in-line, water-cooled, four-stroke	
单缸气门数 Number of single cylinder valves	4	
进气方式 Intake method	增压 Supercharging	增压中冷 Supercharging Intercooling
排量(L) Displacement (L)	3.0	
额定净功率/转速(kW/rpm) Net power/speed rating (kW/rpm)	40.5~74/2300~2500	42~88.3/2200~2600
最大净扭矩/转速(N.M/rpm) Maximum net torque /rpm (N.M/rpm)	450/1300 ~ 1900	
燃油系统 Fuel system	电控高压共轨 Electrically controlled high pressure common rail	
电压制式(V) Voltage system (V)	12/24	